

ARMY RESEARCH LABORATORY



Shock and Vibration Profile for MEF IAS/TCAC PIP

by Stuart Young and
Chris Winslow

ARL-TR-1445

December 1997

DTIC QUALITY INSPECTED 2

19971230 129

Approved for public release; distribution unlimited.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Adelphi, MD 20783-1197

ARL-TR-1445

December 1997

Shock and Vibration Profile for MEF IAS/TCAC PIP

Stuart Young and Chris Winslow
Information Science and Technology Directorate

Approved for public release; distribution unlimited.

Abstract

The Marine Expeditionary Force Intelligence Analysis System (MEF IAS) and the Technical Control and Analysis Center Product Improvement Program (TCAC PIP) are command, control, and intelligence systems developed by the Marine Corps Systems Command and built around a common core system. The development strategy behind the MEF IAS and TCAC PIP is to reduce the total cost of these systems. The major savings will be in life-cycle management costs, by fielding the two different systems to two different organizations within the Marine Corps that share (extensively) a common support structure. This common core system is an M-1097 high-mobility multipurpose wheeled vehicle (HMMWV) (heavy variant) carrying a computer and communications system mounted in a standard integrated command post shelter (SICPS).

This report analyzes the results of tests performed during late 1994 and early 1995. These road tests, rail impact tests, and transit drop tests helped develop a general testing profile that can be applied to future upgrades of the MEF IAS and TCAC PIP. The same technique of using a common core system and individual component testing can be applied to the fielding of entirely new systems. The cost savings of such an approach are significant.

Contents

Introduction	1
Procedure	2
Results	2
Conclusion	4
Bibliography	4
Distribution	53
Report Documentation Page	55

Appendices

A. Plots of Shock Test Results	17
B. Plots of Vibration Test Results	33

Figures

1. Shock response spectrum (SRS): vertical envelope	9
2. SRS: longitudinal envelope	9
3. SRS: transverse envelope	10
4. Vertical: MEF IAS—road data	10
5. Longitudinal: MEF IAS—road data	11
6. Transverse: MEF IAS—road data	11
7. Vertical: TCAC PIP—road data	12
8. Longitudinal: TCAC PIP—road data	12
9. Transverse: TCAC PIP—road data	13
10. MIL-STD-810E: shock spectrum	13
11. MIL-STD-810E: vibration spectrum	14
12. MIL-STD-810E: vibration spectrum	14
13. MIL-STD-810E: vibration spectrum	15

Tables

1. Rail impact tests	5
2. Static drop tests	5
3. Channel locations for rail impact tests (TCAC PIP)	6
4. Channel locations for static drop tests (TCAC PIP)	7
5. Munson road tests	7
6. Channel locations for road runs 1–9	8
7. Channel locations for road runs 12–19	8

Introduction

The Marine Expeditionary Force Intelligence Analysis System (MEF IAS) and the Technical Control and Analysis Center Product Improvement Program (TCAC PIP) are command, control, and intelligence (C²I) systems developed by the Marine Corps Systems Command and built around a common core system. This common core system is an M-1097 high-mobility multipurpose wheeled vehicle (HMMWV) (heavy variant) carrying a computer and communications system mounted in a standard integrated command post shelter (SICPS). The core equipment mounted in the shelter includes computers and associated peripherals, modems, and encryption equipment. Supplied with each vehicle/shelter is a tent that is suitable for connection to the shelter, a number of workstations, and a set of support equipment consisting of tables, chairs, and lights.

The concept behind the development strategy of the MEF IAS and TCAC PIP is one that will reduce the total cost of these systems. While there are savings in design, development, and testing, the major savings will be in life cycle management costs. This savings is achieved by fielding the two different systems to two different organizations within the Marine Corps that share (extensively) a common support structure. This commonality can be found in areas ranging from training to spares inventory.

This core system will be fielded in three variants. The MEF IAS is a two-vehicle system. Each of the two MEF IAS variants contains a slightly different set of peripherals and will be issued with an M101A3 general cargo trailer. The TCAC PIP contains yet a slightly different set of computer peripherals and will be fielded with radios for both voice and data communication. These radios will be mounted in a rack that is a part of the core system. The TCAC PIP will also be fielded with an M101A3 general cargo trailer. The load out for this item will, however, be slightly different than that of the MEF IAS trailer. In each of these three variants, over 85 percent of the components are identical.

The Army Research Laboratory (ARL) has been involved in the design, engineering, and testing of these systems since 1992. During late 1994 and early 1995, a number of mechanical tests were run on the low-rate initial production (LRIP) version of the MEF IAS and TCAC PIP. The prime contractor, in accordance with a government-approved test plan, executed some of the tests at commercial facilities. The government executed some of the tests at the Aberdeen Test Center in Aberdeen, Maryland. Those tests included road tests, rail impact tests, and transit drop tests. All tests were performed in accordance with MIL-STD-810E.¹

In this report, we analyze the results of those tests to develop a general testing profile that can be applied to future upgrades of the MEF IAS and TCAC PIP. The profile to be developed will enable developers to perform component tests rather than full system tests when minor upgrades are

¹Military Standard, *Environmental Test Methods and Engineering Guidelines*, MIL-STD-810E (14 July 1989).

made to the fielded systems. The same technique of using a common core system and individual component testing can be applied to the fielding of entirely new systems. The cost savings of such an approach are significant.

Procedure

We needed to develop a profile that would be the worst case of the test data for the entire interior of the shelter. We developed this profile by calculating the power spectral density (PSD) of each time response for each accelerometer from the Munson road test data (random vibration) for each channel of each test. Next, we assembled the peak response of the interior by enveloping all of the responses for the interior of the shelter. Once the PSD was enveloped, we compared the resulting PSD with MIL-STD-810E and made the final component testing recommendations.

A similar approach was also taken for the shock data. From the time response of the static drop and rail impact tests, we calculated the shock response spectrum (SRS) for each location and then enveloped the responses to find the worst-case response within the shelter. The final SRS profile was then compared with MIL-STD-810E.

The assumption was made that any new components would be mounted to the existing system in such a way as not to further amplify the response of the components. It was also assumed that the components would be installed in the existing equipment racks.

Results

Shock

We investigated the shock test results first. The results from both the rail impact (table 1*) and the static drop tests (table 2) were considered in the shock analysis. The SRS for each location inside the shelter was calculated and then assembled into a single matrix for each of the three orthogonal directions (vertical, longitudinal, and transverse). Only the locations inside the shelter were considered for the analysis. The locations consisted of channels 17 to 34 for the rail impact tests (table 3) and channels 11 to 28 for the static drop tests (table 4). The plots of the test results are shown in appendix A, figures A-1 through A-27. The maximum values are the solid lines, and the dotted lines represent the individual responses for each interior location. Following this analysis, we assembled the peak response and plotted the results as shown in figures 1 to 3. Figure 1 is the vertical orientation, figure 2 is the longitudinal orientation, and figure 3 is the transverse orientation.

*Tables and figures appear at the end of the main body of text (pp. 5 ff).

The LRIP rail impact testing consisted of four tests conducted on the TCAC PIP variant at Aberdeen Proving Ground (APG), Maryland. Combat Systems Test Activity (CSTA) performed the tests in November 1995. The four tests are detailed in table 1. The 30 channels that were instrumented during the rail impact testing are shown in table 3.

The LRIP static drop testing consisted of five tests conducted on the TCAC PIP variant at APG. CSTA performed the tests in November 1995. The five tests are detailed in table 2. Table 4 shows the 24 channels that were instrumented during the static drop testing.

Vibration

We next analyzed the vibration test results. The results from the Munsun road tests (table 5) were considered in this analysis. Both the MEF IAS and TCAC PIP variants were tested, and the results were analyzed separately for each variant. The PSD for each location inside the shelter was calculated and then assembled into a single matrix for each of the three orthogonal directions (vertical, longitudinal, and transverse). Only the locations inside the shelter were considered for the analysis. The locations consisted of channels 1 to 12 for road runs 1 through 9 (table 6), and channels 1 to 12 for road runs 12 through 19 (table 7). The plots of these test results are shown in appendix B, figures B-1 through B-33. The maximum values are the solid lines, and the dotted lines represent the individual responses for each interior location. Following this analysis, we assembled the peak responses for each variant and plotted the results as shown in figures 4 to 9. Figure 4 is the vertical orientation of the MEF IAS, figure 5 is the longitudinal orientation, and figure 6 is the transverse orientation. Similarly, figure 7 is the vertical orientation of the TCAC PIP, figure 8 is the longitudinal orientation, and figure 9 is the transverse orientation.

The PSD results were verified using the following relationship:

$$\sigma^2 = \langle x^2(t)_{rms} \rangle \equiv \int_0^\infty S(f)_{rms} df$$

$$\sim \sum_{\Delta f} S(f)_{rms} \Delta f$$

The LRIP Munsun road testing consisted of 19 tests (11 were analyzed) conducted on the TCAC PIP and MEF IAS variants at Hughes Road Test Facility, California. Honeywell performed the tests in October 1994. The 11 tests are detailed in table 5. Tables 6 and 7 show the 12 channels that were instrumented during the road testing.

Conclusion

A comparison of the test results from this analysis with the profiles from MIL-STD-810E shows that generally the profiles from MIL-STD-810E (fig. 10-13) are more rigorous than the test data. In some instances, however, the actual environment is more severe than the MIL-STD-810E profiles. It should be noted that MIL-STD-810E is suggested input if no data are available and that the profiles in MIL-STD-810E are for inputs to an entire system and not for individual components.

The SRS plots shown in figures 1 to 3 should be used to test any components that need to be installed in the MEF IAS or TCAC PIP. If the components pass these tests, then it is reasonable to assume that the components would survive within the system during a complete system test.

The PSD plots shown in figures 4 to 6 should be used to define tests for any components that may be installed in the MEF IAS. If the components pass these tests, then it is reasonable to assume that the components would survive within the system during a complete system test.

Finally, the PSD plots shown in figures 7 to 9 should be used to define tests for any components that may be installed in the TCAC PIP. If the components pass these tests, then it is reasonable to assume that the components would survive within the system during a complete system test.

Bibliography

- Alvarez, Diane M. (1994). *Abbreviated Test Plan for the Environmental Test of the MEF IAS TCAC PIP*. Aberdeen Proving Ground, MD.
- Alvarez, Diane M. (1995). *Final Report for the Support Test of the MEF IAS TCAC PIP*. Aberdeen Proving Ground, MD.
- Bendat, Julius S., and Allan G. Piersol (1986). *Random Data, Analysis and Measurement Procedures*. New York: John Wiley and Sons.
- Etter, D. M. (1993). *Engineering Problem Solving with MATLAB*. Englewood Cliffs, NJ: Prentice Hall.
- Harris, Cyril M., and Charles E. Crede (1976). *Shock and Vibration Handbook*. New York: McGraw-Hill.
- Inman, Daniel J. (1996). *Engineering Vibration*. Upper Saddle, NJ: Prentice-Hall.
- Robson, J. D. (1964). *An Introduction to Random Vibration*. Edinburgh: Edinburgh University Press, Scotland.
- Vitro Corporation (1995). *Environmental Test Report for the MEF IAS TCAC PIP*. Oxnard, CA.

Table 1. Rail impact tests.

Test	Speed (mph)
1	4.0 forward
2	6.2 forward
3	8.2 forward
4	8.0 reverse

Table 2. Static drop tests.

Test	Orientation
1	Flat
2	Front
3	Rear
4	Curbside
5	Roadside

Table 3. Channel locations for rail impact tests (TCAC PIP).

Channel	Orientation	Location
5	Longitudinal	ECU
6	Transverse	ECU
7	Vertical	ECU
8	Transverse	Shelter ECU frame
9	Longitudinal	Shelter ECU frame
10	Vertical	Shelter ECU frame
11	Longitudinal	HMMWV frame
12	Transverse	HMMWV frame
13	Vertical	HMMWV frame
14	Longitudinal	Floor outside
15	Transverse	Floor outside
16	Vertical	Floor outside
17	Longitudinal	CS rear rack
18	Transverse	CS rear rack
19	Vertical	CS rear rack
20	Longitudinal	CS front rack
21	Transverse	CS front rack
22	Vertical	CS front rack
23	Transverse	BOT disk drive
24	Longitudinal	BOT disk drive
25	Vertical	BOT disk drive
26	Longitudinal	Rack near keyboard
27	Transverse	Rack near keyboard
28	Vertical	Rack near keyboard
29	Longitudinal	RS rack printer
30	Transverse	RS rack printer
31	Vertical	RS rack printer
32	Longitudinal	LG printer base
33	Transverse	LG printer base
34	Vertical	LG printer base

ECU = environmental control unit

HMMWV = high-mobility multipurpose wheeled vehicle

CS = curbside

BOT = bottom

RS = roadside

LG = large

Table 4. Channel locations for static drop tests (TCAC PIP).

Channel	Orientation	Location
5	Longitudinal	HMMWV frame
6	Transverse	HMMWV frame
7	Vertical	HMMWV frame
8	Longitudinal	Floor outside
9	Transverse	Floor outside
10	Vertical	Floor outside
11	Longitudinal	CS rear rack
12	Transverse	CS rear rack
13	Vertical	CS rear rack
14	Longitudinal	CS front rack
15	Transverse	CS front rack
16	Vertical	CS front rack
17	Transverse	BOT disk drive
18	Longitudinal	BOT disk drive
19	Vertical	BOT disk drive
20	Longitudinal	Rack near keyboard
21	Transverse	Rack near keyboard
22	Vertical	Rack near keyboard
23	Longitudinal	RS rack printer
24	Transverse	RS rack printer
25	Vertical	RS rack printer
26	Longitudinal	LG printer
27	Transverse	LG printer
28	Vertical	LG printer

Table 5. Munson road tests.

Run	Description	Speed (mph)	Variant
1	Belgian block	20	MEF IAS
3	Spaced bumps	20	MEF IAS
5	Radial washboard	15	MEF IAS
7	Two-inch washboard	10	MEF IAS
9	Six-inch washboard	5	MEF IAS
12	Belgian block	20	TCAC PIP
13	Spaced bumps	20	TCAC PIP
15	Radial washboard	15	TCAC PIP
16	Two-inch washboard	10	TCAC PIP
18	Six-inch washboard	5	TCAC PIP
19	Pot holes	15	TCAC PIP

Table 6. Channel locations for road runs 1-9.


Channel	Orientation	Location
1	Vertical	Left rear corner
2	Vertical	Center plotter
3	Longitudinal	Left front corner
4	Vertical	Center rack
5	Transverse	Right front corner
6	Vertical	Right rear rack
7	Vertical	Right rear corner
8	Vertical	Center under A/C
9	Transverse	Center rack
10	Longitudinal	Center rack
11	Transverse	Right rear rack
12	Longitudinal	Right rear rack

A/C = air conditioner

Table 7. Channel locations for road runs 12-19.

Channel	Orientation	Location
1	Vertical	Left rear corner
2	Longitudinal	A/C compressor top
3	Longitudinal	Left front corner
4	Vertical	Center rack
5	Vertical	Generator engine mount
6	Vertical	Right rear rack
7	Vertical	Right rear corner
8	Vertical	A/C compressor top
9	Transverse	Center rack
10	Longitudinal	Center rack
11	Transverse	Right rear rack
12	Longitudinal	Right rear rack

**Figure 1. Shock
response spectrum
(SRS): vertical
envelope.**



**Figure 2. SRS:
longitudinal envelope.**




Figure 3. SRS:
transverse envelope.






Figure 4. Vertical: MEF
IAS—road data.



**Figure 5. Longitudinal:
MEF IAS—road data.**



**Figure 6. Transverse:
MEF IAS—road data.**




Figure 7. Vertical:
TCAC PIP—road data.




Figure 8.
Longitudinal: TCAC
PIP—road data.




Figure 9. Transverse:
TCAC PIP—road data.





Figure 10. MIL-STD-810E: shock spectrum.



Test procedure	Peak acceleration (g)	T_E (ms)	Crossover frequency (Hz)
Functional test for flight equipment	20	6–9	45
Functional test for ground equipment	40	6–9	45
Crash hazard test for flight equipment	40	6–9	45
Crash hazard test for ground equipment	75	3.5–5	80

Figure 11. MIL-STD-810E vibration spectrum: overall rms level = 1.04 G.






Figure 12. MIL-STD-810E vibration spectrum: overall rms level = 0.20 G.



Note: If the test item is resonant below 10 Hz, extend the curve to the lowest resonant frequency.

Figure 13. MIL-STD-810E vibration spectrum: overall rms level = 0.74 G.




Note: If the test item is resonant below 10 Hz, extend the curve to the lowest resonant frequency.


Appendix A. Plots of Shock Test Results

These plots show the results of shock tests on the Marine Expeditionary Force Intelligence Analysis System (MEF IAS) and the Technical Control and Analysis Center Product Improvement Program (TCAC PIP) command, control, and intelligence (C²I) systems. The maximum values are the solid lines, and the dotted lines represent the individual responses for each interior location.


**Figure A-1. Rail 1
SRS: vertical
envelope.**



**Figure A-2. Rail 2 SRS:
vertical envelope.**



**Figure A-3. Rail 3 SRS:
vertical envelope.**



**Figure A-4. Rail 4 SRS:
vertical envelope.**




Figure A-5. Drop 1
SRS: vertical envelope.




Figure A-6. Drop 2
SRS: vertical envelope.




Figure A-7. Drop 3
SRS: vertical envelope.







Figure A-8. Drop 4
SRS: vertical envelope.




**Figure A-9. Drop 5 SRS:
vertical envelope.**




**Figure A-10. Rail 1 SRS:
longitudinal envelope.**




**Figure A-11. Rail 2
SRS: longitudinal
envelope.**




**Figure A-12. Rail 3
SRS: longitudinal
envelope.**




**Figure A-13. Rail 4
SRS: longitudinal
envelope.**




**Figure A-14. Drop 1
SRS: longitudinal
envelope.**




**Figure A-15. Drop 2
SRS: longitudinal
envelope.**




**Figure A-16. Drop 3
SRS: longitudinal
envelope.**




**Figure A-17. Drop 4
SRS: longitudinal
envelope.**




**Figure A-18. Drop 5
SRS: longitudinal
envelope.**




**Figure A-19. Rail 1
SRS: transverse
envelope.**




**Figure A-20. Rail 2
SRS: transverse
envelope.**




**Figure A-21. Rail 3 SRS:
transverse envelope.**




**Figure A-22. Rail 4
SRS: transverse
envelope.**




**Figure A-23. Drop 1
SRS: transverse
envelope.**




**Figure A-24. Drop 2
SRS: transverse
envelope.**




**Figure A-25. Drop 3
SRS: transverse
envelope.**



**Figure A-26. Drop 4
SRS: transverse
envelope.**




**Figure A-27. Drop 5
SRS: transverse
envelope.**




Appendix B. Plots of Vibration Test Results

These plots show the results of vibration tests on the Marine Expeditionary Force Intelligence Analysis System (MEF IAS) and the Technical Control and Analysis Center Product Improvement Program (TCAC PIP) command, control, and intelligence (C²I) systems. The maximum values are the solid lines, and the dotted lines represent the individual responses for each interior location.


**Figure B-1. Vertical:
IAS—Belgian block at
20 mph (ROAD001).**




**Figure B-2. Vertical:
IAS—spaced bumps at
20 mph (ROAD003).**




**Figure B-3. Vertical:
IAS—radial
washboard at 15 mph
(ROAD005).**




**Figure B-4. Vertical:
IAS—two-inch
washboard at 10 mph
(ROAD007).**




**Figure B-5. Vertical:
IAS—six-inch
washboard at 5 mph
(ROAD009).**




**Figure B-6. Vertical:
TCAC—Belgian block
at 20 mph (ROAD012).**




**Figure B-7. Vertical:
TCAC—spaced bumps
at 20 mph (ROAD013).**




**Figure B-8. Vertical:
TCAC—radial
washboard at 15 mph
(ROAD015).**




**Figure B-9. Vertical:
TCAC—two-inch
washboard at 10 mph
(ROAD016).**



**Figure B-10. Vertical:
TCAC—six-inch
washboard at 5 mph
(ROAD018).**



**Figure B-11. Vertical:
TCAC—pot holes at
15 mph (ROAD019).**



**Figure B-12.
Longitudinal: IAS—
Belgian block at
20 mph (ROAD001).**




Figure B-13.
Longitudinal: IAS—
spaced bumps at 20 mph
(ROAD003).




Figure B-14.
Longitudinal: IAS—
radial washboard at
15 mph (ROAD005).




Figure B-15.
Longitudinal: IAS—
two-inch washboard
at 10 mph (ROAD007).




Figure B-16.
Longitudinal: IAS—
six-inch washboard
at 5 mph (ROAD009).




Figure B-17.
Longitudinal: TCAC—
Belgian block at
20 mph (ROAD012).




Figure B-18.
Longitudinal: TCAC—
spaced bumps at
20 mph (ROAD013).




Figure B-19.
Longitudinal: TCAC—
radial washboard at
15 mph (ROAD015).




Figure B-20.
Longitudinal: TCAC—
two-inch washboard at
10 mph (ROAD016).




Figure B-21.
Longitudinal: TCAC—
six-inch washboard at
5 mph (ROAD018).




Figure B-22.
Longitudinal: TCAC—
pot holes at 15 mph
(ROAD019).




Figure B-23.
Transverse: IAS—
Belgian block at
20 mph (ROAD001).






Figure B-24.
Transverse: IAS—
spaced bumps at
20 mph (ROAD003).



**Figure B-25. Transverse:
IAS—radial washboard
at 15 mph (ROAD005).**



**Figure B-26. Transverse:
IAS—two-inch
washboard at 10 mph
(ROAD007).**




Figure B-27.
Transverse: IAS—
six-inch washboard at
5 mph (ROAD009).




Figure B-28.
Transverse: TCAC—
Belgian block at
20 mph (ROAD012).




Figure B-29.
 Transverse: TCAC—
 spaced bumps
 at 20 mph (ROAD013).






Figure B-30. Transverse:
 TCAC—radial
 washboard at 15 mph
 (ROAD015).



**Figure B-31. Transverse:
TCAC—two-inch
washboard at 10 mph
(ROAD016).**



**Figure B-32. Transverse:
TCAC—six-inch
washboard at 5 mph
(ROAD018).**





Figure B-33.
Transverse: TCAC—
pot holes at 15 mph
(ROAD019).



Distribution

Admnstr
Defns Techl Info Ctr
Attn DTIC-OCP
8725 John J Kingman Rd Ste 0944
FT Belvoir VA 22060-6218

Ofc of the Secy of Defns
Attn ODDRE (R&AT) G Singley
Attn ODDRE (R&AT) S Gontarek
The Pentagon
Washington DC 20301-3080

MARCORSYSCOM
Attn CCR/IT Project Officer CPT T Sobey
Attn Code CIS D M Hubbs
Attn Code PSE-P G Pardo
Attn Code PSE N Conde
2033 Barnett Ave, Ste 315
Quantico VA 22134-5010

US Army Train & Doctrine Cmd
Battle Lab Integration & Techl Dirctr
Attn ATCD-B J A Klevecz
FT Monroe VA 23651-5850

CECOM RDEC Electronic Systems Div Dir
Attn J Niemela
FT Monmouth NJ 07703

CECOM
Sp & Terrestrial Commctn Div
Attn AMSEL-RD-ST-MC-M H Soicher
FT Monmouth NJ 07703-5203

DARPA
Attn B Kaspar
Attn J Pennella
Attn L Stotts
3701 N Fairfax Dr
Arlington VA 22203-1714

Dpty Assist Scy for Rsrch & Techl
Attn SARD-TT F Milton Rm 3EA79
The Pentagon
Washington DC 20301-0103

DUSD Space
Attn 1E765 J G McNeff
3900 Defense Pentagon
Washington DC 20301-3900

Hdqtrs Dept of the Army
Attn DAMO-FDQ D Schmidt
400 Army Pentagon
Washington DC 20301-0460

MICOM RDEC
Attn AMSMI-RD W C McCorkle
Redstone Arsenal AL 35898-5240

OSD
Attn OUSD(A&T)/ODDDR&E(R) J Lupo
The Pentagon
Washington DC 20301-7100

US Army Aviation Rsrch, Dev, & Engrg Ctr
Attn T L House
4300 Goodfellow Blvd
St Louis MO 63120-1798

US Army CECOM Rsrch, Dev, & Engrg Ctr
Attn R F Giordano
FT Monmouth NJ 07703-5201

US Army Edgewood Rsrch, Dev, & Engrg Ctr
Attn SCBRD-TD J Vervier
Aberdeen Proving Ground MD 21010-5423

US Army Info Sys Engrg Cmd
Attn ASQB-OTD F Jenia
FT Huachuca AZ 85613-5300

US Army Materiel Sys Analysis Agency
Attn AMXSU-D J McCarthy
Aberdeen Proving Ground MD 21005-5071

US Army Matl Cmnd
Dpty CG for RDE Hdqtrs
Attn AMCRD BG Beauchamp
5001 Eisenhower Ave
Alexandria VA 22333-0001

US Army Matl Cmnd Prin
Dpty for Acquisition Hdqtrs
Attn AMCDCG-A D Adams
5001 Eisenhower Ave
Alexandria VA 22333-0001

Distribution (cont'd)

US Army Matl Cmnd
Prin Dpty for Techlgy Hdqtrs
Attn AMCDCG-T M Fisette
5001 Eisenhower Ave
Alexandria VA 22333-0001

US Army Natick Rsrch, Dev, & Engrg Ctr
Acting Techl Dir
Attn SSCNC-T P Brandler
Natick MA 01760-5002

US Army Rsrch Ofc
Attn G Iafrate
4300 S Miami Blvd
Research Triangle Park NC 27709

US Army Simulation, Train, & Instrmntn Cmd
Attn J Stahl
12350 Research Parkway
Orlando FL 32826-3726

US Army Tank-Automotive Cmd Rsrch, Dev,
& Engrg Ctr
Attn AMSTA-TA J Chapin
Warren MI 48397-5000

US Army Tank-Automtv & Armaments Cmd
Attn AMSTA-AR-TD C Spinelli
Bldg 1
Picatinny Arsenal NJ 07806-5000

US Army Test & Eval Cmd
Attn R G Pollard III
Aberdeen Proving Ground MD 21005-5055

US Military Academy
Dept of Mathematical Sci
Attn MAJ D Engen
West Point NY 10996

USAASA
Attn MOAS-AI W Parron
9325 Gunston Rd Ste N319
FT Belvoir VA 22060-5582

GPS Joint Prog Ofc Dir
Attn COL J Clay
2435 Vela Way Ste 1613
Los Angeles AFB CA 90245-5500

Ofc of the Dir Rsrch and Engrg
Attn R Menz
Pentagon Rm 3E1089
Washington DC 20301-3080

Special Assist to the Wing Cmndr
Attn 50SW/CCX CAPT P H Bernstein
300 O'Malley Ave Ste 20
Falcon AFB CO 80912-3020

ARL Electromag Group
Attn Campus Mail Code F0250 A Tucker
University of Texas
Austin TX 78712

Dir for MANPRINT
Ofc of the Deputy Chief of Staff for Personnel
Attn J Hiller
The Pentagon Rm 2C733
Washington DC 20301-0300

US Army Rsrch Lab
Attn AMSRL-CI-LL Tech Lib (3 copies)
Attn AMSRL-CS-AL-TA Mail & Records
Mgmt
Attn AMSRL-CS-AL-TP Techl Pub (3 copies)
Attn AMSRL-IS-CI B Broome
Attn AMSRL-IS-CI C Winslow (2 copies)
Attn AMSRL-IS-CI S Young (2 copies)
Attn AMSRL-IS-P L Tokarick
Attn AMSRL-IS-P T Rose
Attn AMSRL-IS-P R Gregory
Attn AMSRL-IS-P J Locker
Attn AMSRL-IS-P J Van Etten
Attn AMSRL-IS-P S Bragonier
Attn AMSRL-IS-CI T Mills
Adelphi MD 20783-1197

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE December 1997		3. REPORT TYPE AND DATES COVERED Final, April 1997 to June 1997
4. TITLE AND SUBTITLE Shock and Vibration Profile for MEF IAS/TCAC PIP			5. FUNDING NUMBERS PE: 62120A	
6. AUTHOR(S) Stuart Young and Chris Winslow				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Attn: AMSRL-IS-CI (syoung@arl.mil) 2800 Powder Mill Road Adelphi, MD 20783-1197			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-1445	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) MARCORSYSCOM 2033 Barnett Ave, Ste 315 Quantico, VA 22134-5050			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES AMS code: 622120H1600 ARL PR: 7FT330				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The Marine Expeditionary Force Intelligence Analysis System (MEF IAS) and the Technical Control and Analysis Center Product Improvement Program (TCAC PIP) are command, control, and intelligence systems developed by the Marine Corps Systems Command and built around a common core system. The development strategy behind the MEF IAS and TCAC PIP is to reduce the total cost of these systems. The major savings will be in life-cycle management costs, by fielding the two different systems to two different organizations within the Marine Corps that share (extensively) a common support structure. This common core system is an M-1097 high-mobility multipurpose wheeled vehicle (HMMWV) (heavy variant) carrying a computer and communications system mounted in a standard integrated command post shelter (SICPS). This report analyzes the results of tests performed during late 1994 and early 1995. These road tests, rail impact tests, and transit drop tests helped develop a general testing profile that can be applied to future upgrades of the MEF IAS and TCAC PIP. The same technique of using a common core system and individual component testing can be applied to the fielding of entirely new systems. The cost savings of such an approach are significant.				
14. SUBJECT TERMS SICPS, LMS, shelter			15. NUMBER OF PAGES 55	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	